

CKD电磁阀							
序号	防护等级	DC24V/DC100V AC100V,110V/AC200V,220V	气源接口	Cv值或节流孔	环境温度 ℃	接线盒 及接口	备注
1	防水型	AG41-02-2-03AAH	Rc1/4	0.19	-20~+60	无	直动兼用型
2		AG41-02-2-03EA	Rc1/4	0.19	-20~+60	G1/2	直动兼用型
3		AG41-02-2-B4AAH	Rc1/4	0.19	-20~+90	无	直动兼用型
4		AG41-02-2-B4EA	Rc1/4	0.19	-20~+90	G1/2	直动兼用型
5		4F310-08(10)-E2-T	Rc1/4(3/8)	1.35(1.75)	-20~+60	无	
6		4F310-08(10)-B-T	Rc1/4(3/8)	1.35(1.75)	-20~+60	G1/2	
7		4F310-08-B-T-FL	NAMUR	1.35	-20~+60	G1/2	
8		4F510-15-B-T	Rc1/2	2.5	-20~+60	G1/2	
9		4F610-20-B-T	Rc3/4	4.9	-20~+60	G1/2	
10		4F710-25-B-T	Rc1	8.6	-20~+60	G1/2	
11		341N22/4270/485100	NAMUR		-25~+80	G1/2	
12		341N3208/4538/481000	NAMUR		-40~+50	G1/2	
13		4F320-08(10)-E2-T	Rc1/4(3/8)	1.35(1.75)	-20~+60	无	双电控
14		4F320-08(10)-B-T	Rc1/4(3/8)	1.35(1.75)	-20~+60	2-G1/2	双电控
15	隔爆型 dII BT4	AG41E4-02-2-03TA	Rc1/4	0.19	-20~+50	G1/2	直动兼用型
16		4F310E-08(10)-TP-XT	Rc1/4(3/8)	1.35(1.75)	-20~+70	G1/2	
17		4F310E-08-TP-XT-FL	NAMUR	1.35	-20~+70	G1/2	直连式
18		4F510E-15-TP-XT	Rc1/2	2.5	-20~+70	G1/2	
19		4F610E-20-TP-XT	Rc3/4	4.9	-20~+70	G1/2	
20		4F710E-25-TP-XT	Rc1	8.6	-20~+70	G1/2	
21		4F320E-08(10)-TP-XT	Rc1/4(3/8)	1.35(1.75)	-20~+70	2-G1/2	双电控